

Woods BW15.52W Heavy-Duty 15' Batwing™ Slasher

The Woods BW15.52W Batwing™ slasher is a Heavy-Duty Flex Wing slasher built in America with exclusive features that give you an advantage in any field.

Specification	BW15.52W – Heavy Duty
Tractor PTO HP	80-220
Tractor PTO (rpm)	540rpm
Adjustable Cutting Height (mm)	50mm – 380mm
Cutting Capacity (mm)	75mm
Gearbox Rating (hp)	210hp splitter/200hp spindle
Blade Speed (fpm)	540rpm: 15,526 (wing) 15,904 (centre)
Blade Size (mm)	101.6mm x 12.7mm
Blade Overlap (mm)	152mm
Weight (kg)	1,968kg
Transport Width (m) – truck	2.43m (with hydraulics down)
Transport Width (m) – towing	3m (at full height)
Hydraulic Flex Wing	90° up, 22° down
Side Skirt	6.5mm thick, 330mm deep
Stump Jumper	Oval
Wheels	4 x 25.5 severe duty ag foam filled aircraft tyres
Driveline Rating	CAT 6 CV main, CAT 4 wing
Output Shaft Diameter (in)	2 inches
Gearbox Warranty (yrs)	10 years
Structure Warranty (yrs)	2 years

Exclusive Features

- **Unmatched Gearbox Protection:** **10-year warranty** including, parts, labour and seals. Gearbox also features Woods Exclusive **Cool-Flow™** Lubrication Systems and **Triple Seal™** Gearbox Protection.
- **Easy Connection:** The Woods Exclusive **Smartlift™** System holds your 37kg PTO driveline allowing you to easily connect and disconnect from the tractor.
- **Easy Maintenance:** **EZ-Change™** Blade System allows blade change in five steps with a $\frac{3}{4}$ "spanner. No need to oxy or grind blade pins.
- **#1 in Cut Quality:** Enabled deep cutting decks, high-lift blades, structural framing and new features like Woods Exclusive **Level Lock™** Technology ensure a more level cut height across rugged terrain and even distribution of cut material.

Woods Advantages

- **Individual axle sprung wheels:** ensuring an even cut and smooth drive as wheels can absorb impact individually.
- Manufactured in the **United States of America**, assembled in **Australia**.
- 6.5mm thick and 330mm deep side skirt for **maximum handling of cut material**.
- **Full-strength baffled** underside frame ensures a smooth deck surface, minimizing cut material buildup and delivering a **robust, durable slasher**.

The BW15.52W Deck

Underside frame structure keeps the top deck clear to prevent water and debris buildup. Features include replaceable skid shoes, a 6.5 mm thick and 330 mm deep side skirt for optimal material handling, and 1-inch greasable wing pivot pins. The fully baffled deck uses 4.55 mm high-strength steel baffles welded to the frame, plus 3 mm welded baffles for durability under heavy-duty conditions. Manufactured in the USA and assembled in Australia.

A SLASHER IS NOT JUST A SLASHER



Oval stump jumping disc protects the carrier.



Smartlift™ for easy connection to tractor.



Smooth top prevents accumulation of debris. Fully baffled 4.55mm high-strength steel frame. 6.5mm thick and 330mm deep side skirt for maximum handling of cut material.



Individual axle sprung wheels ensuring even cut and wheels individually absorb impact.



Exclusive Level-Lock™ Technology ensures a more level cut height across rugged terrain.



Walterscheid CAT 6 CV main, CAT 4 wing drivelines, 210hp splitter GB, 200hp spindle GB.



Heavy Duty Swivel towing eye reduces stress on equipment.

A SLASHER IS NOT JUST A SLASHER